

Multi Coating Anti Graffiti

PRODUCT INFORMATION:

Multi Coating Anti Graffiti is a UV-resistant and diffusion-open water-based microwax, which prevents graffiti from penetrating the surface. Use Multi Coating ConGuard before Multi Coating Anti Graffiti. Provides up to 8 years of protection.

If tagged on a surface applied with Multi Coating Anti Graffiti, the graffiti can be easily washed off with a high-pressure washer that maintains 60-90 °C. Multi Coating Anti Graffiti is a so-called "sacrificial layer" that is virtually invisible after application. The sacrificial layer must be reapplied after graffiti removal.

AREAS OF USE:

Can be used on most absorbent surfaces such as concrete, marble, brick, sandstone, granite, slate and wood. Both indoors and outdoors.

INSTRUCTIONS FOR USE:

Clean the surface of both graffiti and other contaminants, e.g. traffic dust, grease, oil, varnish paint etc.

Use Multi Coating Graffiti Clean to remove graffiti/tagging from unprotected surfaces.

It is recommended to impregnate the substrate with Multi Coating ConGuard before treating with Multi Coating Anti Graffiti. This will protect the substrate against frost cracking and corrosion, and it will become water-repellent so that no harmful water is pressed into the substrate during graffiti removal.

It is recommended to cover the surfaces that are not to be treated - for example windows.

Recommended application temperature is between 5 - 35°C. Should not be applied at temperatures below +5°C.

Humidity should not exceed 95%.

Shake Multi Coating Anti Graffiti lightly before use. Apply with a low-pressure sprayer, roller or brush, 1-2 layers. The first layer should cure for 30-60 minutes before applying the remaining layers. Can be used on damp surfaces.

NOTE! New concrete must cure for at least 28 days before Multi Coating Anti Graffiti is applied.

On a painted surface, the paint must have cured for 1-4 weeks first, depending on the type of paint.

CURING TIME:

Water-repellent after approx. 2 hours. Dry after 4 hours. Fully cured after 48 hours.

CONSUMPTION: 6 - 12 m² pr/l - depending on the porosity of the surface. Do not thin before use.

Shelf life 24 months in closed original container.

SAFETY:

Wear a mask, goggles and gloves when spraying. Store frost-free and out of reach of children.

All equipment used during application, etc., must be cleaned with clean water after use.

Contains no hazardous substances.