

Multi Coating ConGuard

**PRODUCT INFORMATION:**

Multi Coating ConGuard is a water-based impregnation that is applied to existing surfaces and creates an invisible membrane that increases the service life. The product is designed to absorb and bind to the microscopic pores in the substrate. Water and moisture are actively repelled, which reduces the risk of frost damage. Preserves the surface, while the treated surface maintains its original breathability.

AREAS OF USE:

Paving stones and flagstones, garage floors, concrete facades, concrete elements, concrete and brick roof tiles, natural stone, granite, plastered surfaces, sole benches (concrete/slate).

INSTRUCTIONS FOR USE:

Clean the surface. Allow the surface to dry after cleaning.

Impregnation is applied with a mop, roller, low-pressure sprayer or brush. Multi Coating ConGuard is ready to use and should not be thinned. Must be shaken well before use.

Let the product soak in for 10 - 15 minutes. Then wipe off excess with a dry mop.

On vacuumed and coarsely structured surfaces, additional application can be made immediately.

The impregnation is fully cured after approx. 24 hours. We recommend testing on a small area before full-scale application. Approx. 94.6% diffusion open (i.e. moisture escapes, but not enters).

CONSUMPTION: 8-10 m²/L on concrete.

14-20 m²/L on slate

PH-VALUE: Concentrate: 6.5 - 7.5. PH

SAFETY:

Multi Coating ConGuard is a health & environmentally friendly product. When spraying in closed rooms, it is recommended to wear a dust mask and goggles. Keep out of reach of children. In case of spillage on skin and eyes, rinse with clean water. If swallowed, consult a doctor.

PENETRATION DEPTH: Class II > 10mm

HAZARDOUS ADDITIVES: No hazardous additives according to regulation 1907/2006 REACH

CURLING TIME: Class I > 30%